NSN 5955-01-160-0165

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-160-0165 **Overall Length:** 2.350 inches **Overall Height:** 0.790 inches **Overall Width:** 2.010 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+200.0 **Vibration Resistance Amplitude:** 0.3 inches total excursion **Operating Tempurature Range:** -18.0/+75.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 5820-01-148-3976, radio terminal **Basic Shape Style:** Rectangular or square **Identification Designator:** 954107-5-49956 **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Hermetically sealed **Operating Control Method:** Manual Installation Design: Module **Control Type: Circuit Construction Type:** Solid state Frequency Per Channel: 68.256 megahertz output channel and 69.120 megahertz output channel **Average Power Rating Per Channel:** 0.5 watts input Signal Voltage Rating Per Channel: 0.600 volts output and 1.900 volts output

Impedance Rating Per Channel:

5000.000 ohms operating channel

NSN 5955-01-160-0165

Crystal Controlled Oscillator - Page 2 of 2



Printed circuit bottom

Connection Contact Type And Quantity:

7 printed circuit external

External Dc Operating Voltage In Volts:

5.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200