## NSN 5955-01-160-0168



Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-160-0168 **Overall Length:** 0.887 inches **Overall Height:** 0.400 inches Overall Width: 0.540 inches **Environmental Protection:** Shock resistant and vibration **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 4920-01-128-0375, test set, countermeasures **Basic Shape Style:** Rectangular or square **Identification Designator:** M55310/16-b41a40.000000mhz-81349 **Inclosure Type:** Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel:

40.0 megahertz operating channel

**Connection Type And Location:** 

Err-060 glad hand quick disconnect

**Connection Contact Type And Quantity:** 

14 liters of liquid nitrogen drain

**External Dc Operating Voltage In Volts:** 

4.5 single voltage and 5.5 single voltage

**Test Data Document:** 

81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-o-55310/16 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5955-01-160-0168

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200