NSN 5955-01-166-0089

Overall Length:

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-166-0089

0.300 inches
Overall Diameter:
0.410 inches
Environmental Protection:
Moisture proof
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Training set, electronic warfare an/mst-t1v
Basic Shape Style:
Cylindrical
Identification Designator:
M55310/09-b01a1.000000mhz-81349
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
1.0 megahertz operating channel
Connection Type And Location:
Err-060 glad hand quick disconnect
Connection Contact Type And Quantity:
8 unrc drain
External Dc Operating Voltage In Volts:
4.75 single voltage and 5.25 single voltage
Test Data Document:
81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-o-55310/9 government specification
Shelf Life:
N/a

NSN 5955-01-166-0089

Crystal Controlled Oscillator - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A32200