# NSN 5955-01-166-9213

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-166-9213

# **Overall Length:**

0.778 inches

# **Terminal Length:**

Between 0.223 inches and 0.248 inches

# **Overall Width:**

0.435 inches

## **Body Length:**

0.530 inches

#### **Body Width:**

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

#### **Terminal Diameter:**

# 0.040 inches

#### Mode Of Oscillation:

Fundamental

### **Circuit Resonance:**

Series resonance

# Shunt Capacitance In Picofarads:

7.0

#### Specified Frequency:

5.0688 megahertz

# Holder Cover Material:

Metal

# **Operating Tempurature Range:**

-55.0/+105.0 degrees celsius

# Center To Center Distance Between Terminals:

0.192 inches

# **Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

# Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005

# **Equivalent Resistance Value In Ohms:**

25.0

# Style Designator:

Oval body, pin terminals

# Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Specification Data:

81349-mil-c-3098/63 government specification

# NSN 5955-01-166-9213

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

