NSN 5955-01-170-2332

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-170-2332 **Overall Length:** 0.800 inches **Overall Height:** 0.350 inches **Overall Width:** 0.500 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0/+500.0 **Vibration Resistance Amplitude:** 5.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 30.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** Co238b2-27802 **Maximum Operating Altitude Rating:** 100000.0 feet **Inclosure Type:** Encased **Installation Design:** Module **Circuit Construction Type:** Solid state Frequency Per Channel: 51.2 megahertz operating channel **Signal Voltage Rating Per Channel:** 5.000 volts input **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Solder lug bottom **Connection Contact Type And Quantity:** 14 solder lug external **External Dc Operating Voltage In Volts:**

5.0 single voltage

NSN 5955-01-170-2332

Crystal Controlled Oscillator - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200