## NSN 5955-01-170-3512

Crystal Controlled Oscillator - Page 1 of 2



955-01-170-3512

View Online at https://aerobasegroup.com/nsn/5955
Overall Length:
Between 0.790 inches and 0.800 inches
Overall Height:
0.365 inches
Overall Width:
Between 0.490 inches and 0.500 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Vibration Resistance Amplitude:
20.0 gravitational units
<b>Shock Resistance Rating In Gravitational Units:</b>
1000.0
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
5815-01-098-2796, distributor-transmission
Basic Shape Style:
Rectangular or square
Identification Designator:
M1144-4.9150m-08111
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
4.915 megahertz operating channel
Shock Pulse Duration Time:
0.35 milliseconds
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
4 pin external
External Dc Operating Voltage In Volts:

**External Dc Operating Voltage In Volts:** 

4.5 single voltage and 5.5 single voltage

## NSN 5955-01-170-3512

Crystal Controlled Oscillator - Page 2 of 2



Speci		

Freq stability porm 0.0025 pct

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200