NSN 5955-01-171-8797

Quartz Crystal Unit - Page 1 of 2

Overall Length:

-0.001/+0.001



View Online at https://aerobasegroup.com/nsn/5955-01-171-8797

1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
42.040 megahertz
42.040 megahertz Frequency Tolerance At Reference Tempurature In Percent:
-
Frequency Tolerance At Reference Tempurature In Percent:
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent:
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp:
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range:
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material:
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range:
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals:
Frequency Tolerance At Reference Tempurature In Percent: -0.001/+0.001 Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.478 mils and 0.494 centimeters

NSN 5955-01-171-8797

Quartz Crystal Unit - Page 2 of 2



Equivalent Resistance Value In Ohms

40.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/43 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0