# NSN 5955-01-174-8819

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-174-8819

**Overall Length:** 

0.530 inches

**Terminal Length:** 

0.500 inches

## **Overall Width:**

0.435 inches

### Body Width:

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

#### **Terminal Diameter:**

0.500 inches

#### Mode Of Oscillation:

Fundamental

## **Circuit Resonance:**

Antiresonance

#### Load Capacitance In Picofarads:

Between 31.5 and 32.5

## Shunt Capacitance In Picofarads:

7.0

#### **Specified Frequency:**

11.325 megahertz

#### Holder Cover Material:

Metal

#### **Operating Tempurature Range:**

-55.0/+105.0 degrees celsius

#### **Center To Center Distance Between Terminals:**

0.184 mils and 0.200 centimeters

#### **Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

#### Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005

#### **Equivalent Resistance Value In Ohms:**

25.0

## Style Designator:

Oval body, wire leads

# Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Specification Data:

81349-mil-c-3098/82 government specification

# NSN 5955-01-174-8819

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

