## NSN 5955-01-193-8413

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-193-8413

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
32.0
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
10.3775 megahertz
Holder Cover Material:
Holder Cover Material: Metal
Metal
Metal Operating Tempurature Range:
Metal  Operating Tempurature Range: -55.0/+105.0 degrees celsius
Metal  Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals:
Metal  Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals:  0.486 inches
Metal  Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating:
Metal  Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: 5.0 milliwatts
Metal  Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: 5.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent:
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: 5.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005
Operating Tempurature Range: -55.0/+105.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 5.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms:
Operating Tempurature Range: -55.0/+105.0 degrees celsius  Center To Center Distance Between Terminals: 0.486 inches  Drive Level Rating: 5.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005  Equivalent Resistance Value In Ohms:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5955-01-193-8413

Quartz Crystal Unit - Page 2 of 2



Sı	oec	ific	cati	on	Data:

81349-mil-c-3098/3 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0