## NSN 5955-01-206-0537

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-206-0537

**Overall Length:** 

Between 1.060 inches and 1.085 inches

**Terminal Length:** 

Between 0.273 inches and 0.298 inches

Overall Width:

Between 0.745 inches and 0.750 inches

**Body Width:** 

Between 0.755 inches and 0.775 inches

**Body Thickness:** 

0.315 inches

**Overall Thickness:** 

Between 0.340 inches and 0.345 inches

**Terminal Diameter:** 

Between 0.048 inches and 0.052 inches

**Mode Of Oscillation:** 

Edge shear

**Load Capacitance In Picofarads:** 

34.0

**Shunt Capacitance In Picofarads:** 

7.0

**Specified Frequency:** 

250.000 kilohertz

**Frequency Tolerance At Reference Tempurature In Percent:** 

-0.020/+0.020

**Controlled Reference Temp:** 

81.0 degrees celsius

**Operable Tempurature Range:** 

-20.0/+150.0 degrees fahrenheit

**Holder Cover Material:** 

Metal

**Operating Tempurature Range:** 

-22.0/+140.0 degrees fahrenheit

**Center To Center Distance Between Terminals:** 

0.468 inches

**Drive Level Rating:** 

2.0 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.020/+0.020

Style Designator:

Oval body, pin terminals

Shelf Life:

N/a

## NSN 5955-01-206-0537

Quartz Crystal Unit - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0