NSN 5955-01-208-2378

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-208-2378

Overall Length:	
Between 0.998 inches and 1.023 inches	
Terminal Length:	
Between 0.223 inches and 0.248 inches	
Overall Width:	
0.757 inches	
Body Length:	
0.775 inches	
Body Width:	
0.725 inches	
Body Thickness:	
0.317 inches	
Overall Thickness:	
0.352 inches	
Terminal Diameter:	
Between 0.048 inches and 0.052 inches	
Mode Of Oscillation:	
Fundamental	
Circuit Resonance:	
Antiresonance	
Load Capacitance In Picofarads:	
Between 31.5 and 32.5	
Shunt Capacitance In Picofarads:	
7.0	
Specified Frequency:	
11.755 megahertz	
Holder Cover Material:	
Metal or glass	
Operating Tempurature Range:	
-55.0/+105.0 degrees celsius and -55.0/+125.0 degrees celsius	
Center To Center Distance Between Terminals:	
0.478 mils and 0.494 centimeters	
Drive Level Rating:	
Between 4.0 milliwatts and 6.0 milliwatts	
Frequency Tolerance For Operating Tempurature In Percent:	
-0.005/+0.005 and -0.0010/+0.0010	
Equivalent Resistance Value In Ohms:	
22.0	
Style Designator:	
Square body	

Test Data Document:

81349-mil-c-3098/62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5955-01-208-2378

Quartz Crystal Unit - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

81349-mil-c-3098/35 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0