Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-213-2261

Overall Length:
Between 0.790 inches and 0.800 inches
Overall Height:
0.365 inches
Overall Width:
Between 0.490 inches and 0.500 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Vibration Resistance Range In Hertz:
+10.0 to 2000.0
Vibration Resistance Amplitude:
20.0 gravitational units
Shock Resistance Rating In Gravitational Units:
1000.0
Operating Tempurature Range:
+0.0 to 70.0 degrees celsius
Storage Tempurature Range:
-55.0 to 125.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
M1145-4.800000mhz-08111
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Mechanical
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
4.8 megahertz operating channel
Shock Pulse Duration Time:
0.35 milliseconds
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
4 pin external

Crystal Controlled Oscillator - Page 2 of 2



External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200