

NSN 5955-01-214-2483 Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-214-2483 **Overall Length:** 0.815 inches **Overall Height:** 0.373 inches **Overall Width:** 0.515 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0 to 2000.0 **Vibration Resistance Amplitude:** 20.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 1000.0 **Operating Tempurature Range:** +0.0 to 70.0 degrees celsius **Storage Tempurature Range:** -55.0 to 125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** M1145-20m-08111 **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic

Installation Design:

Module

**Control Type:** 

Remote

**Circuit Construction Type:** 

Solid state

Frequency Per Channel:

20.0 megahertz operating channel

**Shock Pulse Duration Time:** 

0.35 milliseconds

**Connection Type And Location:** 

Pin bottom

**Connection Contact Type And Quantity:** 

4 pin external

## NSN 5955-01-214-2483

Crystal Controlled Oscillator - Page 2 of 2



External Dc Operating Voltage In Volts:
---

4.5 single voltage and 5.5 single voltage

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32200