NSN 5955-01-226-6848

Quartz Crystal Unit - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5955-01-226-6646 |
|---|
| Overall Length: |
| 0.530 inches |
| Terminal Length: |
| 0.500 inches |
| Overall Width: |
| 0.435 inches |
| Body Width: |
| 0.402 inches |
| Body Thickness: |
| 0.150 inches |
| Overall Thickness: |
| 0.183 inches |
| Terminal Diameter: |
| 0.017 inches |
| Mode Of Oscillation: |
| Third overtone |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| 4.0 |
| Specified Frequency: |
| 39.250 megahertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -55.0/+105.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.192 inches |
| Drive Level Rating: |
| 2.0 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.0005/+0.0005 |
| Equivalent Resistance Value In Ohms: |
| 40.0 |
| Style Designator: |
| Oval body, wire leads |
| Test Data Document: |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-c-3098/87 government specification |

N/a

Shelf Life:

NSN 5955-01-226-6848

Quartz Crystal Unit - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A059a0