NSN 5955-01-227-5183

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-227-5183

| Overall Length: |
|---|
| 0.530 inches |
| Terminal Length: |
| 0.500 inches |
| Overall Width: |
| 0.435 inches |
| Body Width: |
| 0.402 inches |
| Body Thickness: |
| 0.150 inches |
| Overall Thickness: |
| 0.183 inches |
| Terminal Diameter: |
| Between 0.016 inches and 0.019 inches |
| Mode Of Oscillation: |
| Fifth overtone |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| 7.0 |
| Specified Frequency: |
| 68.6875 megahertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -55.0/+105.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.184 mils and 0.200 centimeters |
| Drive Level Rating: |
| Between 1.6 milliwatts and 2.4 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.005/+0.005 |
| Equivalent Resistance Value In Ohms: |
| 50.0 |
| Style Designator: |
| Oval body, wire leads |
| Test Data Document: |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-c-3098/34 government specification |

N/a

Shelf Life:

NSN 5955-01-227-5183

Quartz Crystal Unit - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A059a0