## NSN 5955-01-227-6711



Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-227-6711 **Overall Length:** 0.780 inches **Overall Diameter:** 0.410 inches **Environmental Protection:** Moisture proof **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Cylindrical **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic **Installation Design:** Module **Circuit Construction Type:** Solid state Frequency Per Channel: 5.0 megahertz operating channel **Connection Type And Location:** Err-060 glad hand quick disconnect **Connection Contact Type And Quantity:** 8 liters of liquid nitrogen drain **External Dc Operating Voltage In Volts:** 4.5 single voltage and 5.5 single voltage **Special Features:** length includes 0.480 in. Pin length **Test Data Document:** 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-o-55310/9 government specification Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5955-01-227-6711

Crystal Controlled Oscillator - Page 2 of 2



Fiig:

A32200