NSN 5955-01-234-7884

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-234-7884

| Overall Length: |
|---|
| 0.525 inches |
| Terminal Length: |
| 1.500 inches |
| Overall Width: |
| 0.428 inches |
| Body Width: |
| Between 0.394 inches and 0.401 inches |
| Body Thickness: |
| Between 0.142 inches and 0.149 inches |
| Overall Thickness: |
| 0.176 inches |
| Terminal Diameter: |
| 0.019 inches |
| Mode Of Oscillation: |
| Fundamental |
| Circuit Resonance: |
| Antiresonance |
| Load Capacitance In Picofarads: |
| 32.0 |
| Shunt Capacitance In Picofarads: |
| 7.0 |
| Specified Frequency: |
| 2.4576 megahertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -55.0/+105.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.192 inches |
| Drive Level Rating: |
| 5.0 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.005/+0.005 |
| Equivalent Resistance Value In Ohms: |
| 250.0 |
| Style Designator: |
| Oval body, wire leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5955-01-234-7884

Quartz Crystal Unit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

