NSN 5955-01-246-3314

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-246-3314 **Overall Length:** 0.800 inches **Overall Height:** 0.200 inches **Overall Width:** 0.500 inches **Environmental Protection:** Vibration and shock resistant **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** Co-401a-2b-20mhz-27802 **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 16.0 kilohertz input channel and 100.0 megahertz output channel **Shock Pulse Duration Time:** 6.0 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 4 pin external **External Dc Operating Voltage In Volts:** 5.0 single voltage Shelf Life: N/a **Unit Of Measure:**

--

NSN 5955-01-246-3314

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200