Crystal Controlled Oscillator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-01-246-8180

Overall Length: 2.660 inches Overall Height: 0.570 inches Overall Width: 2.000 inches Environmental Protection: Dustproof and explosion proof and moisture proof and shock resistant and vibration Operating Tempurature Range:
Overall Height: 0.570 inches Overall Width: 2.000 inches Environmental Protection: Dustproof and explosion proof and moisture proof and shock resistant and vibration
0.570 inches Overall Width: 2.000 inches Environmental Protection: Dustproof and explosion proof and moisture proof and shock resistant and vibration
Overall Width: 2.000 inches Environmental Protection: Dustproof and explosion proof and moisture proof and shock resistant and vibration
2.000 inchesEnvironmental Protection:Dustproof and explosion proof and moisture proof and shock resistant and vibration
Environmental Protection: Dustproof and explosion proof and moisture proof and shock resistant and vibration
Dustproof and explosion proof and moisture proof and shock resistant and vibration
Operating Tempurature Range:
-54.0/+71.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
A-161900-2-94987
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
55.170197 megahertz operating channel
Connection Type And Location:
Pin bottom and receptacle, coaxial left side
Connection Contact Type And Quantity:
2 pin external and 1 receptacle, coaxial external
External Dc Operating Voltage In Volts:
15.0 single voltage
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200