Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-247-7419

Overall Length:	
0.887 inches	
Overall Height:	
0.400 inches	
Overall Width:	
0.540 inches	
Environmental Prote	ection:
Moisture proof	
Operating Tempurat	ure Range:
-55.0/+125.0 degrees	celsius
Storage Tempuratur	e Range:
-62.0/+125.0 degrees	celsius
Average Life Measu	rement:
Not rated	
Basic Shape Style:	
Rectangular or square	3
Inclosure Type:	
Hermetically sealed	
Operating Control N	ethod:
Automatic	
Installation Design:	
Module	
Circuit Construction	Туре:
Solid state	
Frequency Per Char	nel:
6.144 megahertz ope	rating channel
Connection Type Ar	d Location:
Err-060 glad hand qu	ck disconnect
Connection Contact	Type And Quantity:
14 liters of liquid nitro	gen drain
External Dc Operation	ng Voltage In Volts:
4.5 single voltage an	15.5 single voltage
Test Data Document	:
81349-mil-o-55310 sp	ecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes con	mercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and pe	rformance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:	
81349-mil-o-55310/16	government specification
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
Yes - demil/mli	

NSN 5955-01-247-7419

Crystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

