Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-252-6998

C	Overall Length:
C	.887 inches
C	Overall Height:
C	.400 inches
C	Overall Width:
С	.540 inches
E	Invironmental Protection:
Ν	loisture proof
C	Operating Tempurature Range:
-:	55.0/+125.0 degrees celsius
S	Storage Tempurature Range:
-	62.0/+125.0 degrees celsius
A	verage Life Measurement:
٨	lot rated
E	Basic Shape Style:
F	Rectangular or square
h	nclosure Type:
ŀ	lermetically sealed
C	Operating Control Method:
A	utomatic
h	nstallation Design:
Ν	lodule
C	Control Type:
F	Remote
C	Circuit Construction Type:
S	Solid state
F	requency Per Channel:
4	1.38 megahertz operating channel
C	Connection Type And Location:
E	rr-060 glad hand quick disconnect
C	Connection Contact Type And Quantity:
1	4 liters of liquid nitrogen drain
E	External Dc Operating Voltage In Volts:
4	.5 single voltage and 5.5 single voltage
T	est Data Document:
8	1349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
f	ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
e	nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
S	pecification Data:
8	1349-mil-o-55310/16 government specification
S	shelf Life:
٨	I/a

Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200