Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-257-0164

Overall Length:	
Between 0.790 inches and 0.800 inches	
Overall Height:	
0.365 inches	
Overall Width:	
Between 0.490 inches and 0.500 inches	
Environmental Protection:	
Moisture proof and shock resistant and vibration	
Vibration Resistance Range In Hertz:	
+10.0/+2000.0	
Vibration Resistance Amplitude:	
20.0 gravitational units	
Shock Resistance Rating In Gravitational Units:	
1000.0	
Operating Tempurature Range:	
+0.0/+70.0 degrees celsius	
Storage Tempurature Range:	
-55.0/+125.0 degrees celsius	
Average Life Measurement:	
Not rated	
Basic Shape Style:	
Rectangular or square	
Identification Designator:	
M1200-10.368mhz-08111	
Inclosure Type:	
Hermetically sealed	
Operating Control Method:	
Automatic	
Installation Design:	
Module	
Control Type:	
Remote	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
10.368 megahertz operating channel	
Shock Pulse Duration Time:	
0.35 milliseconds	
Connection Type And Location:	
Pin bottom	
Connection Contact Type And Quantity:	
4 pin external	

Crystal Controlled Oscillator - Page 2 of 2



External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

Special Features:

Freq stability porm 0.01 pct

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200