NSN 5955-01-257-0166

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-257-0166 **Overall Length:** 0.800 inches **Overall Height:** 0.450 inches **Overall Width:** 0.500 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +55.0/+2000.0 **Vibration Resistance Amplitude:** 20.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 500.0 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+140.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic **Installation Design:** Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 2.4576 megahertz operating channel **Shock Pulse Duration Time:** 1.0 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 4 pin external **External Dc Operating Voltage In Volts:**

4.75 single voltage and 5.25 single voltage

NSN 5955-01-257-0166

Crystal Controlled Oscillator - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200