NSN 5955-01-257-3592



Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-01-257-3592 **Overall Length:** 0.887 inches **Overall Height:** 0.400 inches **Overall Width:** 0.540 inches **Environmental Protection:** Moisture proof **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 10.0 kilohertz operating channel **Connection Type And Location:** Err-060 glad hand quick disconnect **Connection Contact Type And Quantity:** 14 liters of liquid nitrogen drain **External Dc Operating Voltage In Volts:** 10.8 single voltage and 13.2 single voltage **Test Data Document:** 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-o-55310/18 government specification

Shelf Life:

N/a

Unit Of Measure:

NSN 5955-01-257-3592

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200