Crystal Controlled Oscillator - Page 1 of 2



data in specification

View Online at https://aerobasegroup.com/nsn/5955-01-261-1556

Overall Leng	th:
0.887 inches	
Overall Heig	ht:
0.400 inches	
Overall Widt	h:
0.540 inches	
	al Protection:
Moisture proc	f
Operating Te	empurature Range:
-55.0/+125.0	degrees celsius
Storage Tem	purature Range:
-62.0/+125.0	degrees celsius
Average Life	Measurement:
Not rated	
Basic Shape	Style:
Rectangular of	or square
Inclosure Ty	pe:
Hermetically	sealed
Operating Co	ontrol Method:
Automatic	
Installation [	Design:
Module	
Control Type	r.
Remote	
<b>Circuit Cons</b>	truction Type:
Solid state	
Frequency P	er Channel:
10.75 megah	ertz operating channel
Connection	Type And Location:
	nand quick disconnect
-	Contact Type And Quantity:
	uid nitrogen drain
	Operating Voltage In Volts:
	Itage and 5.5 single voltage
Test Data Do	
	5310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
	des commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	I and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification	
-	i5310/16 government specification
Shelf Life:	So ro, re government appointation
N/a	

## Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200