Crystal Controlled Oscillator - Page 1 of 2



specification certain

View Online at https://aerobasegroup.com/nsn/5955-01-261-4027

Ove	erall Length:
0.8	37 inches
Ove	erall Height:
0.4	00 inches
Ove	erall Width:
0.5	40 inches
Env	vironmental Protection:
Мо	sture proof
Ор	erating Tempurature Range:
-55	0/+125.0 degrees celsius
Sto	rage Tempurature Range:
-62	0/+125.0 degrees celsius
Ave	erage Life Measurement:
Not	rated
Bas	sic Shape Style:
Red	stangular or square
Inc	losure Type:
Her	metically sealed
Ор	erating Control Method:
Aut	omatic
Ins	allation Design:
Mo	dule
Со	ntrol Type:
Rer	note
Cir	cuit Construction Type:
Sol	d state
Fre	quency Per Channel:
3.0	megahertz operating channel
Со	nnection Type And Location:
Err	060 glad hand quick disconnect
Со	nnection Contact Type And Quantity:
14	iters of liquid nitrogen drain
Ext	ernal Dc Operating Voltage In Volts:
4.5	single voltage and 5.5 single voltage
Tes	t Data Document:
813	49-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in s
forr	nat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on
env	ironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Spe	ecification Data:
813	49-mil-o-55310/16 government specification
She	elf Life:
N/a	

Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200