## NSN 5955-01-261-7068

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-261-7068

Overall Length:				
1.223 inches				
Terminal Length:				
0.448 inches				
Overall Width:				
0.757 inches				
Body Length:				
0.775 inches				
Body Width:				
0.725 inches				
Body Thickness:				
0.317 inches				
Overall Thickness:				
0.352 inches				
Terminal Diameter:				
Between 0.091 inches and 0.095 inches				
Mode Of Oscillation:				
Fundamental				
Circuit Resonance:				
Antiresonance				
Load Capacitance In Picofarads:				
Between 12.5 and 13.5				
Specified Frequency:				
7.425 megahertz				
Holder Cover Material:				
Metal				
Operating Tempurature Range:				
-40.0/+70.0 degrees celsius				
Center To Center Distance Between Terminals:				
0.478 mils and 0.494 centimeters				
Drive Level Rating:				
Between 27.0 milliwatts and 55.0 milliwatts				
Frequency Tolerance For Operating Tempurature In Percent:				
-0.005/+0.005				
Equivalent Resistance Value In Ohms:				
70.0				
Style Designator:				
Oval body, pin terminals				
Test Data Document:				
81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;				
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental				
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).				

## Specification Data:

81349-mil-c-3098/78 government specification

## NSN 5955-01-261-7068

Quartz Crystal Unit - Page 2 of 2



		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0