## NSN 5955-01-261-7151

Quartz Crystal Unit - Page 1 of 2

81349-mil-c-3098/76 government specification

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5955-01-261-7151

| 1.937 inches  |
|---|
| Terminal Length:  |
| Between 0.625 inches and 0.655 inches   |
| Overall Width:  |
| 1.170 inches  |
| Body Length:  |
| 1.282 inches  |
| Body Width:   |
| 1.125 inches  |
| Body Thickness:   |
| 0.411 inches  |
| Overall Thickness:  |
| 0.460 inches  |
| Terminal Diameter:  |
| Between 0.123 inches and 0.127 inches   |
| Mode Of Oscillation:  |
| Fundamental   |
| Circuit Resonance:  |
| Antiresonance   |
| Load Capacitance In Picofarads:   |
| Between 34.5 and 35.5   |
| Specified Frequency:  |
| 5.820 megahertz   |
| Holder Cover Material:  |
| Metal   |
| Operating Tempurature Range:  |
| -55.0/+90.0 degrees celsius   |
| Center To Center Distance Between Terminals:  |
| 0.490 mils and 0.510 centimeters  |
| Drive Level Rating:   |
| Between 45.0 milliwatts and 55.0 milliwatts   |
| Frequency Tolerance For Operating Tempurature In Percent:   |
| -0.005/+0.005   |
| Equivalent Resistance Value In Ohms:  |
| 60.0  |
| Style Designator:   |
| Oval body, pin terminals  |
| Test Data Document:   |
| 81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Specification Data:   |

## NSN 5955-01-261-7151

Quartz Crystal Unit - Page 2 of 2



| _ |   |   |     | - |      |  |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. |   | ife: |  |
|   |   |   |     |   |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0