## NSN 5955-01-261-8236

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-261-8236

| Overall Length:   |  |  |  |  |  |  |
|---|--|--|--|--|--|--|
| 1.937 inches  |  |  |  |  |  |  |
| Terminal Length:  |  |  |  |  |  |  |
| Between 0.625 inches and 0.655 inches   |  |  |  |  |  |  |
| Overall Width:  |  |  |  |  |  |  |
| 1.170 inches  |  |  |  |  |  |  |
| Body Length:  |  |  |  |  |  |  |
| 1.282 inches  |  |  |  |  |  |  |
| Body Width:   |  |  |  |  |  |  |
| 1.125 inches  |  |  |  |  |  |  |
| Body Thickness:   |  |  |  |  |  |  |
| 0.411 inches  |  |  |  |  |  |  |
| Overall Thickness:  |  |  |  |  |  |  |
| 0.460 inches  |  |  |  |  |  |  |
| Terminal Diameter:  |  |  |  |  |  |  |
| Between 0.123 inches and 0.127 inches   |  |  |  |  |  |  |
| Mode Of Oscillation:  |  |  |  |  |  |  |
| Fundamental   |  |  |  |  |  |  |
| Circuit Resonance:  |  |  |  |  |  |  |
| Antiresonance   |  |  |  |  |  |  |
| Load Capacitance In Picofarads:   |  |  |  |  |  |  |
| Between 34.5 and 35.5   |  |  |  |  |  |  |
| Specified Frequency:  |  |  |  |  |  |  |
| 8.20941 megahertz   |  |  |  |  |  |  |
| Holder Cover Material:  |  |  |  |  |  |  |
| Metal   |  |  |  |  |  |  |
| Operating Tempurature Range:  |  |  |  |  |  |  |
| -55.0/+90.0 degrees celsius   |  |  |  |  |  |  |
| Center To Center Distance Between Terminals:  |  |  |  |  |  |  |
| 0.490 mils and 0.510 centimeters  |  |  |  |  |  |  |
| Drive Level Rating:   |  |  |  |  |  |  |
| Between 27.0 milliwatts and 33.0 milliwatts   |  |  |  |  |  |  |
| Frequency Tolerance For Operating Tempurature In Percent:   |  |  |  |  |  |  |
| -0.005/+0.005   |  |  |  |  |  |  |
| Equivalent Resistance Value In Ohms:  |  |  |  |  |  |  |
| 30.0  |  |  |  |  |  |  |
| Style Designator:   |  |  |  |  |  |  |
| Oval body, pin terminals  |  |  |  |  |  |  |
| Test Data Document:   |  |  |  |  |  |  |
| 81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |  |  |  |  |  |  |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |  |  |  |  |  |  |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |  |  |  |  |  |  |

81349-mil-c-3098/76 government specification

**Specification Data:** 

## NSN 5955-01-261-8236

Quartz Crystal Unit - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0