## NSN 5955-01-265-1403

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-265-1403

| Overall Length:                                                                                                                                   |  |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|
| 1.223 inches                                                                                                                                      |  |  |  |  |  |
| Terminal Length:                                                                                                                                  |  |  |  |  |  |
| 0.448 inches                                                                                                                                      |  |  |  |  |  |
| Overall Width:                                                                                                                                    |  |  |  |  |  |
| 0.757 inches                                                                                                                                      |  |  |  |  |  |
| Body Length:                                                                                                                                      |  |  |  |  |  |
| 0.775 inches                                                                                                                                      |  |  |  |  |  |
| Body Width:                                                                                                                                       |  |  |  |  |  |
| 0.725 inches                                                                                                                                      |  |  |  |  |  |
| Body Thickness:                                                                                                                                   |  |  |  |  |  |
| 0.317 inches                                                                                                                                      |  |  |  |  |  |
| Overall Thickness:                                                                                                                                |  |  |  |  |  |
| 0.352 inches                                                                                                                                      |  |  |  |  |  |
| Terminal Diameter:                                                                                                                                |  |  |  |  |  |
| Between 0.091 inches and 0.095 inches                                                                                                             |  |  |  |  |  |
| Mode Of Oscillation:                                                                                                                              |  |  |  |  |  |
| Fundamental                                                                                                                                       |  |  |  |  |  |
| Circuit Resonance:                                                                                                                                |  |  |  |  |  |
| Antiresonance                                                                                                                                     |  |  |  |  |  |
| Load Capacitance In Picofarads:                                                                                                                   |  |  |  |  |  |
| Between 24.5 and 25.5                                                                                                                             |  |  |  |  |  |
| Specified Frequency:                                                                                                                              |  |  |  |  |  |
| 4.255 megahertz                                                                                                                                   |  |  |  |  |  |
| Holder Cover Material:                                                                                                                            |  |  |  |  |  |
| Metal                                                                                                                                             |  |  |  |  |  |
| Operating Tempurature Range:                                                                                                                      |  |  |  |  |  |
| -55.0/+90.0 degrees celsius                                                                                                                       |  |  |  |  |  |
| Center To Center Distance Between Terminals:                                                                                                      |  |  |  |  |  |
| 0.478 mils and 0.494 centimeters                                                                                                                  |  |  |  |  |  |
| Drive Level Rating:                                                                                                                               |  |  |  |  |  |
| Between 45.0 milliwatts and 55.0 milliwatts                                                                                                       |  |  |  |  |  |
| Frequency Tolerance For Operating Tempurature In Percent:                                                                                         |  |  |  |  |  |
| -0.005/+0.005                                                                                                                                     |  |  |  |  |  |
| Equivalent Resistance Value In Ohms:                                                                                                              |  |  |  |  |  |
| 100.0                                                                                                                                             |  |  |  |  |  |
| Style Designator:                                                                                                                                 |  |  |  |  |  |
| Oval body, pin terminals                                                                                                                          |  |  |  |  |  |
| Test Data Document:                                                                                                                               |  |  |  |  |  |
| 81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |  |  |  |  |  |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |  |  |  |  |  |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                                               |  |  |  |  |  |

## **Specification Data:**

81349-mil-c-3098/77 government specification

## NSN 5955-01-265-1403

Quartz Crystal Unit - Page 2 of 2



| C | ha  | Ιf | 1 | ife   |  |
|---|-----|----|---|-------|--|
| • | ııe |    | _ | .II C |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0