## NSN 5955-01-265-1410

Quartz Crystal Unit - Page 1 of 2

**Specification Data:** 

81349-mil-c-3098/77 government specification



View Online at https://aerobasegroup.com/nsn/5955-01-265-1410

Overall Length:
1.223 inches
Terminal Length:
0.448 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.091 inches and 0.095 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 24.5 and 25.5
Specified Frequency:
4.780 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-55.0/+90.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
Between 45.0 milliwatts and 55.0 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.005/+0.005
Equivalent Resistance Value In Ohms:
75.0
Style Designator:
Oval body, pin terminals
Test Data Document:
81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5955-01-265-1410

Quartz Crystal Unit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0