# NSN 5955-01-265-4430

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-265-4430

# **Overall Length:**

1.023 inches

## **Terminal Length:**

Between 0.223 inches and 0.248 inches

## **Overall Width:**

0.757 inches

## **Body Length:**

0.775 inches

#### **Body Width:**

0.725 inches

#### Body Thickness:

0.317 inches

#### **Overall Thickness:**

0.352 inches

#### **Terminal Diameter:**

## 0.050 inches

#### Mode Of Oscillation:

Fundamental

# **Circuit Resonance:**

Antiresonance

## Load Capacitance In Picofarads:

32.0

#### Shunt Capacitance In Picofarads:

7.0

### Specified Frequency:

11.7775 megahertz

### Holder Cover Material:

Metal

#### **Operating Tempurature Range:**

-55.0/+105.0 degrees celsius

#### **Center To Center Distance Between Terminals:**

0.486 inches

#### **Drive Level Rating:**

5.0 milliwatts

# Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005

### **Equivalent Resistance Value In Ohms:**

22.0

# Style Designator:

Oval body, pin terminals

# **Test Data Document:**

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5955-01-265-4430

Quartz Crystal Unit - Page 2 of 2



**Specification Data:** 

81349-mil-c-3098/3 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0