# NSN 5955-01-265-4447

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-265-4447

# **Overall Length:**

0.778 inches

# **Terminal Length:**

Between 0.223 inches and 0.248 inches

# **Overall Width:**

0.435 inches

### **Body Length:**

0.530 inches

#### **Body Width:**

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

#### **Terminal Diameter:**

0.040 inches

#### Mode Of Oscillation:

Fifth overtone and third overtone

#### Circuit Resonance:

Series resonance

# Shunt Capacitance In Picofarads:

7.0

#### Specified Frequency:

68.2425 megahertz

# Holder Cover Material:

Metal or glass

# **Operating Tempurature Range:**

-40.0/+90.0 degrees celsius and -55.0/+105.0 degrees celsius

# **Center To Center Distance Between Terminals:**

0.192 inches

# **Drive Level Rating:**

Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts

# Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002 and -0.003/+0.003

# Equivalent Resistance Value In Ohms:

60.0

# Test Data Document:

81349-mil-c-3098/62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-c-3098/60 government specification

# Shelf Life:

N/a

# NSN 5955-01-265-4447

Quartz Crystal Unit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0

