NSN 5955-01-265-4475

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-265-4475

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
32.0
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
1.056 megahertz
Frequency Tolerance At Reference Tempurature In Percent:
-0.002/+0.002
-0.002/+0.002
-0.002/+0.002 Frequency Stability In Percent:
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp:
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range:
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material:
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range:
-0.002/+0.002 Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius

5.0 milliwatts

NSN 5955-01-265-4475

Quartz Crystal Unit - Page 2 of 2



_		•		
Freguency	Tolerance Fo	or Operating	Tempurature	In Percent:

-0.002/+0.002

Equivalent Resistance Value In Ohms:

540.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/9 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A059a0