## NSN 5955-01-266-7873

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-266-7873

| Overall Length:   |
|---|
| Between 0.998 inches and 1.023 inches   |
| Terminal Length:  |
| Between 0.223 inches and 0.248 inches   |
| Overall Width:  |
| 0.757 inches  |
| Body Length:  |
| 0.775 inches  |
| Body Width:   |
| 0.725 inches  |
| Body Thickness:   |
| 0.317 inches  |
| Overall Thickness:  |
| 0.352 inches  |
| Terminal Diameter:  |
| Between 0.048 inches and 0.052 inches   |
| Mode Of Oscillation:  |
| Fundamental   |
| Circuit Resonance:  |
| Antiresonance   |
| Load Capacitance In Picofarads:   |
| Between 31.5 and 32.5   |
| Specified Frequency:  |
| 1.048576 megahertz  |
| Holder Cover Material:  |
| Metal   |
| Operating Tempurature Range:  |
| -55.0/+105.0 degrees celsius  |
| Center To Center Distance Between Terminals:  |
| 0.478 mils and 0.494 centimeters  |
| Drive Level Rating:   |
| Between 8.0 milliwatts and 12.0 milliwatts  |
| Frequency Tolerance For Operating Tempurature In Percent:   |
| -0.005/+0.005   |
| Equivalent Resistance Value In Ohms:  |
| 540.0   |
| Style Designator:   |
| Oval body, pin terminals  |
| Test Data Document:   |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/3 government specification

## NSN 5955-01-266-7873

Quartz Crystal Unit - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0