NSN 5955-01-272-6122

Quartz Crystal Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-01-272-6122

Overall Length:
0.265 inches
Terminal Length:
Between 0.150 inches and 0.180 inches
Diameter:
0.335 inches
Overall Diameter:
0.420 inches
Terminal Diameter:
Between 0.016 inches and 0.019 inches
Mode Of Oscillation:
Fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
4.5
Specified Frequency:
81.002604 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
Operating Tempurature Range: +0.0/+65.0 degrees celsius
+0.0/+65.0 degrees celsius
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals:
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating:
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent:
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms:
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: Between 28.0 and 45.0
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: Between 28.0 and 45.0 Style Designator:
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: Between 28.0 and 45.0 Style Designator: Hat type, 3 wire leads
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: Between 28.0 and 45.0 Style Designator: Hat type, 3 wire leads Shelf Life:
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: Between 28.0 and 45.0 Style Designator: Hat type, 3 wire leads Shelf Life: N/a
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: Between 28.0 and 45.0 Style Designator: Hat type, 3 wire leads Shelf Life: N/a
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: Between 28.0 and 45.0 Style Designator: Hat type, 3 wire leads Shelf Life: N/a Unit Of Measure:
+0.0/+65.0 degrees celsius Center To Center Distance Between Terminals: 0.190 mils and 0.210 centimeters Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.001/+0.001 Equivalent Resistance Value In Ohms: Between 28.0 and 45.0 Style Designator: Hat type, 3 wire leads Shelf Life: N/a Unit Of Measure: Demilitarization: