# NSN 5955-01-274-6436

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-274-6436

# Overall Length:

0.530 inches

# **Terminal Length:**

Between 1.000 inches and 1.120 inches

# **Overall Width:**

0.435 inches

#### **Body Width:**

0.402 inches

#### Body Thickness:

0.150 inches

# **Overall Thickness:**

0.183 inches

#### **Terminal Diameter:**

Between 0.015 inches and 0.019 inches

# Mode Of Oscillation:

Fundamental

#### **Circuit Resonance:**

Antiresonance

# Load Capacitance In Picofarads:

Between 31.5 and 32.5

# Shunt Capacitance In Picofarads:

7.0

#### **Specified Frequency:**

9.000 megahertz

# Holder Cover Material:

Metal

# **Operating Tempurature Range:**

+20.0/+70.0 degrees celsius

# Center To Center Distance Between Terminals:

0.184 mils and 0.200 centimeters

# **Drive Level Rating:**

Between 2.0 milliwatts and 3.0 milliwatts

# Frequency Tolerance For Operating Tempurature In Percent:

-0.0025/+0.0025

# **Equivalent Resistance Value In Ohms:**

35.0

# Style Designator:

Oval body, wire leads

# Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Specification Data:

81349-mil-c-3098/116 government specification

# NSN 5955-01-274-6436

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0

