Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-285-9147

Overall Length:	
0.887 inches	
Overall Height:	
0.400 inches	
Overall Width:	
0.540 inches	
Environmental Protection:	
Moisture proof	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-62.0/+125.0 degrees celsius	
Average Life Measurement:	
Not rated	
Basic Shape Style:	
Rectangular or square	
Inclosure Type:	
Hermetically sealed	
Operating Control Method:	
Automatic	
Installation Design:	
Module	
Control Type:	
Remote	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
512.0 kilohertz operating channel	
Connection Type And Location:	
Err-060 glad hand quick disconnect	
Connection Contact Type And Quantity:	
14 liters of liquid nitrogen drain	
External Dc Operating Voltage In Volts:	
4.5 single voltage and 5.5 single voltage	
Test Data Document:	
81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification	ation type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting gene	eral type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", '	"", etc.).
Specification Data:	
81349-mil-o-55310/16 government specification	
Shelf Life:	
N/a	

Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200