NSN 5955-01-291-1874

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-291-1874 **Overall Length:** Between 0.950 inches and 1.250 inches **Overall Height:** 0.120 inches **Overall Width:** 0.650 inches **Environmental Protection:** Moisture proof **Operating Tempurature Range:** -55.0/+105.0 degrees celsius Storage Tempurature Range: -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

16.0 megahertz operating channel

Connection Type And Location:

Err-060 threaded internal and err-060 yoke

Connection Contact Type And Quantity:

20 liters of liquid nitrogen drain

External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

Test Data Document:

81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-o-55310/21 government specification

Shelf Life:

N/a

Unit Of Measure:

NSN 5955-01-291-1874

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200