Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-297-6798

| ngth:  |
|--|
| -9<br>19   |
| ight:  |
|  |
| dth:   |
|  |
| ental Protection:  |
| oof  |
| Tempurature Range:   |
| 0 degrees celsius  |
| empurature Range:  |
| 0 degrees celsius  |
| fe Measurement:  |
|  |
| be Style:  |
| r or square  |
|  |
| y sealed   |
| Control Method:  |
|  |
| n Design:  |
| · · · · ·  |
| pe:  |
|  |
| nstruction Type:   |
|  |
| Per Channel:   |
| ertz operating channel   |
| n Type And Location:   |
| d hand quick disconnect  |
| n Contact Type And Quantity:   |
| iquid nitrogen drain   |
| c Operating Voltage In Volts:  |
| voltage and 5.5 single voltage   |
| Document:  |
| o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| sludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| tal and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| on Data:   |
| o-55310/14 government specification  |
|  |
|  |
|  |

## Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200