Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-297-8614

0	overall Length:
	.887 inches
	overall Height:
	.400 inches
	overall Width:
	.540 inches
	nvironmental Protection:
	loisture proof
	perating Tempurature Range:
	55.0/+125.0 degrees celsius
	torage Tempurature Range:
	55.0/+125.0 degrees celsius
	verage Life Measurement:
N	lot rated
В	asic Shape Style:
R	ectangular or square
Ir	nclosure Type:
Н	lermetically sealed
0	perating Control Method:
A	utomatic
Ir	nstallation Design:
N	lodule
С	control Type:
R	lemote
С	Sircuit Construction Type:
S	olid state
F	requency Per Channel:
8	3.2 kilohertz operating channel
С	connection Type And Location:
E	rr-060 glad hand quick disconnect
С	connection Contact Type And Quantity:
1	4 liters of liquid nitrogen drain
Е	xternal Dc Operating Voltage In Volts:
4	.75 single voltage and 5.25 single voltage
S	pecial Features:
ł	neight includes 0.200 in. Pin length
Т	est Data Document:
8	1349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-o-55310/14 government specification

Shelf Life:

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32200