NSN 5955-01-305-7208

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-305-7208
Overall Length:
Between 1.749 inches and 1.774 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
1.526 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 19.5 and 20.5
Shunt Capacitance In Picofarads:
1.6
Specified Frequency:
32.768 kilohertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-40.0/+70.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
0.1 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.012/+0.012
Equivalent Resistance Value In Ohms:
110000.0
Style Designator:
Oval body, pin terminals
Test Data Document:
81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5955-01-305-7208

Quartz Crystal Unit - Page 2 of 2



O :	£! 1!	D-1-
Speci	fication	Data:
opoo.		

81349-mil-c-3098/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0