NSN 5955-01-305-7299

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-305-7299 **Overall Length:** 0.820 inches **Overall Height:** Between 0.465 inches and 0.525 inches **Overall Width:** 0.520 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +55.0/+2000.0 **Vibration Resistance Amplitude:** 35.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 1000.0 **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Storage Tempurature Range:** -55.0/+85.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 4920-01-187-4068 test system, automatic, radar **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 40.0 megahertz operating channel **Shock Pulse Duration Time:** 0.35 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 4 pin external

NSN 5955-01-305-7299

Crystal Controlled Oscillator - Page 2 of 2



Evtornal	DcO	neratina	Voltage	In Valte	
=xternar	טט טע	beraunu	voitaue	III VOILS	

5.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200