

View Online at <https://aerobasegroup.com/nsn/5955-01-306-1105>

Overall Length:

0.775 inches

Terminal Length:

1.500 inches

Overall Width:

0.757 inches

Body Width:

0.725 inches

Body Thickness:

0.317 inches

Overall Thickness:

0.352 inches

Terminal Diameter:

0.050 inches

Mode Of Oscillation:

Fundamental

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

20.0

Shunt Capacitance In Picofarads:

7.0

Specified Frequency:

2.040 megahertz

Holder Cover Material:

Metal

Operating Temperature Range:

-55.0/+105.0 degrees celsius

End Application:

Nondirectional beacon (xmtr), model sr515 (ndbsr515)

Center To Center Distance Between Terminals:

0.486 inches

Drive Level Rating:

10.0 milliwatts

Frequency Tolerance For Operating Temperature In Percent:

-0.005/+0.005

Equivalent Resistance Value In Ohms:

270.0

Style Designator:

Oval body, wire leads

Test Data Document:

81349-cr18au2-040mhz specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0