Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-309-5944

0.815 inchesOverall Height:0.450 inchesOverall Width:0.516 inchesEnvironmental Protection:Moisture proof and shock resistant and vibrationVibration Resistance Range In Hertz:+55.0/+2000.0Vibration Resistance Amplitude:10.0 gravitational unitsShock Resistance Rating In Gravitational Units:100.0Operating Tempurature Range:-55.0/+125.0 degrees celsiusStorage Tempurature Range:-65.0/+150.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style:Rectangular or squareInclosure Type:Hermetically sealedOperating Control Method:AutomaticInstallation Design:ModuleCincuit Construction Type:Solid stateFrequency Per Channel:40.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottom	Overall Length:
0.450 inchesOverall Width:0.516 inchesEnvironmental Protection:Moisture proof and shock resistant and vibrationVibration Resistance Range In Hertz:+55.0/+2000.0Vibration Resistance Amplitude:10.0 gravitational unitsShock Resistance Rating In Gravitational Units:10.0 gravitational unitsShock Resistance Rating In Gravitational Units:10.0.0Operating Tempurature Range:-55.0/+125.0 degrees celsiusStorage Tempurature Range:-65.0/+150.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style:Rectangular or squareInclosure Type:Hermetically sealedOperating Control Method:AutomaticInstallation Design:ModuleCincuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottom	-
0.450 inchesOverall Width:0.516 inchesEnvironmental Protection:Moisture proof and shock resistant and vibrationVibration Resistance Range In Hertz:+55.0/+2000.0Vibration Resistance Amplitude:10.0 gravitational unitsShock Resistance Rating In Gravitational Units:10.0 gravitational unitsShock Resistance Rating In Gravitational Units:10.0.0Operating Tempurature Range:-55.0/+125.0 degrees celsiusStorage Tempurature Range:-65.0/+150.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style:Rectangular or squareInclosure Type:Hermetically sealedOperating Control Method:AutomaticInstallation Design:ModuleCincuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottom	Overall Height:
0.516 inches Environmental Protection: Moisture proof and shock resistant and vibration Vibration Resistance Range In Hertz: +55.0/+2000.0 Vibration Resistance Amplitude: 10.0 gravitational units Shock Resistance Rating In Gravitational Units: 100.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	-
Environmental Protection: Moisture proof and shock resistant and vibration Vibration Resistance Range In Hertz: +55.0/+2000.0 Vibration Resistance Amplitude: 10.0 gravitational units Shock Resistance Rating In Gravitational Units: 100.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Overall Width:
Moisture proof and shock resistant and vibrationVibration Resistance Range In Hertz: +55.0/+2000.0Vibration Resistance Amplitude:10.0 gravitational unitsShock Resistance Rating In Gravitational Units:100.0Operating Tempurature Range: -55.0/+125.0 degrees celsiusStorage Tempurature Range: -65.0/+150.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style: Rectangular or squareInclosure Type: Hermetically sealedOperating Control Method: AutomaticModuleControl Type: RemoteRemoteGricuit Construction Type: Solid state400.0 kilohertz operating channelShock Pulse Duration Time: 6.0 millisecondsConnection Type And Location: Pin bottomPin bottomConnection Contact Type And Quantity:	0.516 inches
Vibration Resistance Range In Hertz: +55.0/+2000.0 Vibration Resistance Amplitude: 10.0 gravitational units Shock Resistance Rating In Gravitational Units: 100.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Environmental Protection:
Vibration Resistance Range In Hertz: +55.0/+2000.0 Vibration Resistance Amplitude: 10.0 gravitational units Shock Resistance Rating In Gravitational Units: 100.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Moisture proof and shock resistant and vibration
+55.0/+2000.0 Vibration Resistance Amplitude: 10.0 gravitational units Shock Resistance Rating In Gravitational Units: 100.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	
 10.0 gravitational units Shock Resistance Rating In Gravitational Units: 100.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Adudue Control Type: Remote Gircuit Construction Type: Solid state Frequency Per Channel: Autol, kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom 	-
Shock Resistance Rating In Gravitational Units: 100.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: Autonalic Frequency Per Channel: Autonalic Gonection Type And Location: Pin bottom	Vibration Resistance Amplitude:
Shock Resistance Rating In Gravitational Units: 100.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: Autonalic Frequency Per Channel: Autonalic Gonection Type And Location: Pin bottom	10.0 gravitational units
Operating Tempurature Range:-55.0/+125.0 degrees celsiusStorage Tempurature Range:-65.0/+150.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style:Rectangular or squareInclosure Type:Hermetically sealedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteGreuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottom	Shock Resistance Rating In Gravitational Units:
 -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom 	100.0
Storage Tempurature Range: -65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Operating Tempurature Range:
-65.0/+150.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	
Average Life Measurement:Not ratedBasic Shape Style:Rectangular or squareInclosure Type:Hermetically sealedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottomConnection Contact Type And Quantity:	Storage Tempurature Range:
Not ratedBasic Shape Style:Rectangular or squareInclosure Type:Hermetically sealedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottomConnection Contact Type And Quantity:	-65.0/+150.0 degrees celsius
Basic Shape Style:Rectangular or squareInclosure Type:Hermetically sealedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottomConnection Contact Type And Quantity:	Average Life Measurement:
Rectangular or square Inclosure Type: Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Not rated
Inclosure Type:Hermetically sealedOperating Control Method:AutomaticAutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottomConnection Contact Type And Quantity:	Basic Shape Style:
Hermetically sealed Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Rectangular or square
Operating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottomConnection Contact Type And Quantity:	Inclosure Type:
AutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateFrequency Per Channel:400.0 kilohertz operating channelShock Pulse Duration Time:6.0 millisecondsConnection Type And Location:Pin bottomConnection Contact Type And Quantity:	Hermetically sealed
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Operating Control Method:
Module Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Automatic
Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom	Installation Design:
Remote Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom Connection Contact Type And Quantity:	Module
Circuit Construction Type: Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom Connection Contact Type And Quantity:	Control Type:
Solid state Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom Connection Contact Type And Quantity:	Remote
Frequency Per Channel: 400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom Connection Contact Type And Quantity:	Circuit Construction Type:
400.0 kilohertz operating channel Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom Connection Contact Type And Quantity:	Solid state
Shock Pulse Duration Time: 6.0 milliseconds Connection Type And Location: Pin bottom Connection Contact Type And Quantity:	Frequency Per Channel:
6.0 milliseconds Connection Type And Location: Pin bottom Connection Contact Type And Quantity:	400.0 kilohertz operating channel
Connection Type And Location: Pin bottom Connection Contact Type And Quantity:	Shock Pulse Duration Time:
Pin bottom Connection Contact Type And Quantity:	6.0 milliseconds
Connection Contact Type And Quantity:	Connection Type And Location:
	Pin bottom
	Connection Contact Type And Quantity:
4 pin external	4 pin external
External Dc Operating Voltage In Volts:	External Dc Operating Voltage In Volts:
	4.5 single voltage and 5.5 single voltage
	4.5 single voltage and 5.5 single voltage

NSN 5955-01-309-5944

Crystal Controlled Oscillator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200