## NSN 5955-01-311-1364

Crystal Controlled Oscillator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5955-01-311-1364  |
|--|
| Overall Length:  |
| Between 0.635 inches and 0.665 inches  |
| Overall Height:  |
| 0.085 inches   |
| Overall Width:   |
| Between 0.635 inches and 0.665 inches  |
| Environmental Protection:  |
| Moisture proof   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -62.0/+125.0 degrees celsius   |
| Average Life Measurement:  |
| Not rated  |
| Basic Shape Style:   |
| Rectangular or square  |
| Inclosure Type:  |
| Hermetically sealed  |
| Operating Control Method:  |
| Automatic  |
| Installation Design:   |
| Module   |
| Control Type:  |
| Remote   |
| Circuit Construction Type:   |
| Solid state  |
| Frequency Per Channel:   |
| 3.6864 megahertz operating channel   |
| Connection Type And Location:  |
| Err-060 glad hand quick disconnect   |
| Connection Contact Type And Quantity:  |
| 44 liters of liquid nitrogen drain   |
| External Dc Operating Voltage In Volts:  |
| 4.5 single voltage and 5.5 single voltage  |
| Test Data Document:  |
| 81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-o-55310/20 government specification  |
| Shelf Life:  |
| N/a  |

-

**Unit Of Measure:** 

## NSN 5955-01-311-1364

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200