Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-313-9916

Overall Length:
5.500 inches
Overall Height:
2.000 inches
Overall Width:
2.000 inches
Environmental Protection:
Fungus proof and moisture proof and salt spray resistant and shock resistant and vibration
Operating Tempurature Range:
-20.0/+90.0 degrees celsius
Storage Tempurature Range:
-57.0/+71.0 degrees celsius
Average Life Measurement:
Indefinite
End Application:
5805-01-187-9399 switchboard, telephone
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
9.216 megahertz operating channel
Connection Type And Location:
Connector, plug bottom
Connection Contact Type And Quantity:
18 pin external
External Dc Operating Voltage In Volts:
5.0 1st voltage err-100
Criticality Code Justification:
Feat
Special Features:
Nuclear hardness critical item
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 5955-01-313-9916

Crystal Controlled Oscillator - Page 2 of 2

Fiig: A32200

