

View Online at <https://aerobasegroup.com/nsn/5955-01-314-3213>

Overall Length:

Between 0.790 inches and 0.800 inches

Overall Height:

0.230 inches

Overall Width:

Between 0.490 inches and 0.500 inches

Environmental Protection:

Moisture proof and shock resistant and vibration

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Vibration Resistance Amplitude:

20.0 gravitational units

Shock Resistance Rating In Gravitational Units:

1000.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Storage Temperature Range:

-55.0/+125.0 degrees celsius

Average Life Measurement:

Not rated

End Application:

1430-01-286-1314 guided missile battery control central, vehicle mounted

Basic Shape Style:

Rectangular or square

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

10.0 megahertz operating channel

Shock Pulse Duration Time:

0.35 milliseconds

Connection Type And Location:

Pin bottom

Connection Contact Type And Quantity:

4 pin external

External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200