NSN 5955-01-314-3214

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-314-3214 **Overall Length:** 0.800 inches **Overall Height:** 0.500 inches **Overall Width:** 0.350 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +0.0/+500.0 **Vibration Resistance Amplitude:** 10.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 1260-01-208-6448 mast mounted sight **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic **Installation Design:** Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 2.4576 megahertz operating channel **Shock Pulse Duration Time:** 6.0 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 14 pin external **External Dc Operating Voltage In Volts:**

5.0 single voltage

NSN 5955-01-314-3214

Crystal Controlled Oscillator - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200