
Crystal Controlled Oscillator - Page 1 of 1



### **Overall Length:**

Between 0.465 inches and 0.495 inches

### **Overall Height:**

0.085 inches

## Overall Width:

Between 0.465 inches and 0.495 inches

#### **Operating Tempurature Range:**

-55.0/+105.0 degrees celsius

#### Average Life Measurement:

Not rated

#### **Basic Shape Style:**

Rectangular or square

#### Inclosure Type:

Hermetically sealed

#### **Operating Control Method:**

### Automatic

Installation Design:

Module

Control Type:

Remote

### **Circuit Construction Type:**

Solid state

### Frequency Per Channel:

18.0 megahertz operating channel

### **Connection Type And Location:**

Err-060 glad hand quick disconnect

### **Connection Contact Type And Quantity:**

40 liters of liquid nitrogen drain

# External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

# Test Data Document:

81349-mil-o-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Specification Data:

81349-mil-o-55310/19 government specification

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

## Fiig:

A32200

